

Dye Sublimation 8 in 1 Heat Press

Directions below are an indication of what can be expected when pressing a Ceramicraft 11oz white Sublimation mug. Settings used are Start temp 180°C, End Temp 180°C and 270 seconds (medium pressure). It is always advisable to test your own heat press and find the best settings to suit.

Preparation

- 1. Check the heat press in the machine against the sublimation blank to be pressed
- 2. If the heat mat requires changing, it is a simple process of removing the existing mat and bracket and replacing with the correct size/shape.
- 3. Attach the new heat pad to the power supply
- 4. Before commencing the pressing process check the pressure setting against pressing instructions

Control Box Operation

- 1. Turn on machine. Switch at side of control panel digital display will illuminate and begin flashing
- Set end temperature by pressing the MODE button twice. Temperature display will flash and may be altered by using the +/- buttons
- 3. Set **Time** by pressing the MODE button again. Time display will flash and may be altered by using the +/- buttons
- 4. Press MODE button to return to the "current temperature"
- 5. To set the **start temperature** press the MODE button once. Temperature display will flash and may be altered by using the +/- buttons. (start temp is always set lower or the same as the end temp)
- 6. Press MODE two more times to review the end temperature and time
- 7. Return to the "current temperature"
- 8. Temperature will slowly rise and begin beeping when ready to place mug in press
- 9. Insert mug and clamp press
- 10. Time will begin to count down
- 11. Once finished, release mug and allow to cool

Heater sizes:

- Straight-Shaped Mugs 5-10oz: 5-7.5cm
- Straight-Shaped Mugs 11-22oz : 7.5-9cm
- Cone-Shaped Latte Mug 12 oz: 9*H9.8cm
- Cone-Shaped Latte Mug 17oz: 8.8*H14.9cm
- Round Press 12cm for 7.5" Plate
- Round Press 15cm for 10" Plate
- Flat Press Plate 30*38cm
- Cap press 14*8.5cm

Voltage: 240V Plug: 10amp Weight: 27kg